

NAVRTKA 1 kom						
/	standard JUS601 DIN934	samokočiva JUS622 DIN985	zatvorena JUS627 DIN1587	leptir JUS680 DIN315	unit navrtka	niska navrtka jus 604
M 3	0.11	-	-	-	-	0.11
M 4	0.19	0.50	1.15	-	-	0.20
M 5	0.26	0.54	1.18	2.21	-	0.27
M 6	0.44	0.65	1.40	2.57	2.10	0.40
M 8	0.94	1.40	2.96	3.57	3.60	0.86
M 10	2.08	3.10	5.00	6.25	4.60	1.73
M 12	3.05	4.50	9.13	12.1	-	2.55
M 14	4.43	6.50	13.1	-	-	-
M 16	6.00	9.00	18.00	-	-	4.62
M 18	8.75	-	-	-	-	-
M 20	11.5	19.0	-	-	-	-
M 22	14.0	-	-	-	-	-
M 24	20.7	-	-	-	-	-
M 27	32.5	-	-	-	-	-
M 30	48.0	-	-	-	-	-

Masinski vijak jus 103-130-118					
Dimenz	3	4	5	6	8
8	0.30	0.40	0.70	-	-
10	0.35	0.40	0.70	1.10	-
16	-	0.55	0.85	1.30	1.62
20	-	0.60	1.00	1.50	1.85
25	-	0.70	1.15	1.70	2.20
30	-	0.80	1.20	1.80	2.57
40	-	1.00	1.50	2.15	3.16
50	-	1.12	1.90	2.60	3.80
60	-	1.40	2.20	3.00	4.45
70	-	-	-	3.00	5.30

UKUCAVAJUCI TIPL 1 kom			
Dimen	6	8	10
40	1.80	-	-
60	2.30	4.00	-
80	3.20	4.50	8.30
100	4.25	5.35	9.35
120	-	6.70	10.60
140	-	7.80	12.60